

## AS7312-54XS Switch 25GbE Data Center Switch Bare-Metal Hardware



### Product Overview

The Edgecore AS7312-54XS switch is a Top-of-Rack (TOR) or spine switch for high-performance data centers. In a compact 1RU form factor, the switch provides line-rate L2 and L3 switching across the 48 x2 5GbE SFP28 with 6x100GbE QSFP28, supporting up to 48 x 10/25 GbE, 6 x 40/100 GbE connections. The AS7312-54XS can be deployed as a TOR switch supporting 10/25 GbE to servers with 40/100 GbE uplinks, or as a spine switch supporting 40/100 GbE spine interconnects. This open network switch is loaded with the Open Network Install Environment (ONIE) which supports the installation of compatible Network Operating System software, including the open source options Open Network Linux and OpenSwitch, plus commercial NOS offerings.

### Key Features and Benefits

- Cost-effective, bare-metal switch infrastructure for data center fabric.
- Deploy as Top-of-Rack switch supporting 10 or 25 GbE to servers, with 40 or 100 GbE uplinks.
- Deploy as spine switch supporting 10, 25, 40, or 100 GbE ToR and spine interconnects.
- 48 x 25G SFP28 plus 6 x 100G QSFP28 ports, each SFP28 supporting 1 x 10 or 25 GbE and each QSFP28 supporting 1 x 100G or 1 x 40G.
- Layer 2 or Layer 3 forwarding of 3.6 Tbps full duplex.
- Supports hot/cold aisle with port-to-power and power-to-port airflow SKUs.
- All ports on front; PSUs and fans accessible from rear.
- Hot-swappable, load-sharing, redundant AC or -48V DC or 12V DC PSUs.
- 5+1 redundant, hot-swappable fan modules.
- Bare-Metal hardware switch pre-loaded with diagnostics software and with Open Network Install Environment (ONIE) for automated loading of compatible open source and commercial NOS offerings.  
Compatible with Open Network Linux (ONL), the open-source, OCP reference NOS.  
Compatible with Cumulus® Linux® r3.6 and later version.  
Compatible with PicOS™ from Pica8 Inc.  
Compatible with SnapRoute CN-NOS, Cloud Native - NOS, software.

Data Center Switch



## Features

### Ports

Switch Ports:

- 48 x 25G SFP28 plus 6 x 100G QSFP28 ports:
  - Each SFP28 supports 1 x 10 G or 25 GbE
  - Each QSFP28 supports 1x40/100 GbE or 4 x 25 GbE or 4 x 10 GbE per port using splitter cables

Management ports on port side:

- 1 x RJ-45 serial console
- 1 x RJ-45 100/1000BASE-T management
- 1 x USB Type A storage

### Key Components

Switch Silicon: Broadcom BCM56967 Tomahawk+

No PHYs, No Retimers

CPU Modules:

- Intel Atom® C2538 quad-core 2.4 GHz x86 processor
- DDR3: 8 GB x 2 SO-DIMM with ECC
- SPI NOR Flash: 8 MB x 2
- mSATA: 32 GB MLC

### Performance

- Switching Capacity: 3.6 Tbps full duplex
- Forwarding Rate: 2.6 Bpps
- Jumbo frames support up to 9216 Bytes
- Packet Buffer Size: 22 MB integrated packet buffer
- Subject to NOS:
- MAC Addresses: 8K min./136K max.
- VLAN IDs: 4 K
- IPv4/32: 16 K L3 LPM entries with TCAM-only mode
- IPv6/64: 8 K L3 LPM entries with TCAM-only mode
- IPv6/128: 4 K L3 LPM entries with TCAM-only mode

### Physical and Environmental

- Dimensions (WxDxH): 43.84 x 47.3 x 4.35 cm (17.26 x 18.62 x 1.73 in)
- Weight: 9.43 kg (20.78 lb), with two installed PSUs
- Fans: 5+1 redundant, hot-swappable
- Operating Temperature: 0°C to 45°C (32°F to 113°F)
- Storage Temperature: -40°C to 70°C (-40°F to 158°F)
- Operating Humidity: 5% to 95% non-condensing

### Software

- Diagnostics
- Compatible with the following NOS options:
  - Open Network Linux, the open-source, OCP reference NOS
  - Compatible with Cumulus® Linux® r3.6 and later version
  - Compatible with PicOS™ from Pica8 Inc
  - Compatible with SnapRoute CN-NOS, Cloud Native - NOS, software.

### LEDs

- 10G SFP+ Port LEDs: Link Speed, Link Status, Activity
- 25G SFP28 Port LEDs: Link Status, Activity for 25G status
- 100G QSFP28 Port LEDs: Link Status, Activity for 100G status
- 100G QSFP28 Breakout LEDs: show Link, Status, Activity with 4 x 25G breakout
- Ethernet Management Port LED: Link Status, Activity
- System LEDs: Diagnostic, Locator, PSU and Fan Status

### Power

- PSUs: 2 redundant, load-sharing, hot-swappable AC or -48 VDC
- Input Voltage: 90 to 240 VAC at 50-60 Hz. -36 to -72 VDC
- PSU Efficiency: Up to 93% for AC PSUs
- Power input option: 12 VDC
- The total estimated power budget is around 511 W

### Regulatory

- EMI
  - CE Mark
  - EN55032 Class A
  - EN55024
  - EN61000-3-2
  - EN61000-3-3
  - FCC Part 15 Subpart B Class A
  - VCCI Class A
  - CCC
- Safety
  - CB
  - UL/CUL
  - CCC
  - BSMI
- Environmental:
  - NEBS GR63-CORE (Pre-test)
- RoHS-6 Compliant
- Country of Origin: Taiwan (TAA Compliant)
- WEEE Standards: The switches complied with the following WEEE standards: Waste Electrical and Electronic Equipment (WEEE Directive 2002/96/EC)

### Warranty

Please check [www.edge-core.com](http://www.edge-core.com) for the warranty terms in your country.

### For More Information

To find out more about Edgecore Networks Corporation products and solutions, visit [www.edge-core.com](http://www.edge-core.com).

### About Edgecore Networks Corporation

Edgecore Networks Corporation is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edgecore Networks Corporation delivers the software and systems that transform the way the world connects. Edgecore Networks Corporation serves customers and partners worldwide. Additional information can be found at [www.edge-core.com](http://www.edge-core.com).

Edgecore Networks Corporation is a subsidiary of Accton Technology Corporation, the leading network ODM company. The Edgecore Data Center switches are developed and manufactured by Accton.

To purchase Edgecore Networks solutions, please contact your Edgecore Networks Corporation representatives at +886 3 563 8888 (HQ) or +1 (949)-336-6801 or authorized resellers.

© Copyright 2018 Edgecore Networks Corporation. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edgecore Networks Corporation. Edgecore Networks Corporation shall not be liable for technical or editorial errors or omissions contained herein.

## Ordering Information

**Base Model: AS7312-54XS 48-Port 25G SFP28 with 6 x 100G QSFP uplinks; ONIE software installer**

Model Number	CPU Module	PSU	Airflow	Region (power cord)
7312-54XS-O-AC-F-US	Intel Atom® C2538 processor	Dual AC PSUs	Port-to-Power airflow	N. America
7312-54XS-O-AC-B-US	Intel Atom® C2538 processor	Dual AC PSUs	Power-to-Port airflow	N. America
7312-54XS-O-AC-F-EU	Intel Atom® C2538 processor	Dual AC PSUs	Port-to-Power airflow	Europe
7312-54XS-O-AC-B-EU	Intel Atom® C2538 processor	Dual AC PSUs	Power-to-Port airflow	Europe
7312-54XS-O-AC-F-UK	Intel Atom® C2538 processor	Dual AC PSUs	Port-to-Power airflow	UK
7312-54XS-O-AC-B-UK	Intel Atom® C2538 processor	Dual AC PSUs	Power-to-Port airflow	UK
7312-54XS-O-AC-F-JP	Intel Atom® C2538 processor	Dual AC PSUs	Port-to-Power airflow	Japan
7312-54XS-O-AC-B-JP	Intel Atom® C2538 processor	Dual AC PSUs	Power-to-Port airflow	Japan
7312-54XS-O-48V-F	Intel Atom® C2538 processor	Dual 48 VDC PSUs port-to-power airflow		
7312-54XS-O-48V-B	Intel Atom® C2538 processor	Dual 48 VDC PSUs power-to-port airflow		
7312-54XS-O-12V-F	Intel Atom® C2538 processor	One 12 VDC power input port-to-power airflow		
7312-54XS-O-12V-B	Intel Atom® C2538 processor	One 12 VDC power input power-to-port airflow		