

S9701-82DC

DISAGGREGATED CORE/EDGE ROUTER

The S9701-82DC is the best of breed robust, flexible and carrier-grade disaggregated IP/MPLS router that can be deployed in the core or edge to transport services over a scalable next-gen service provider network. Equipped with 25GE and 100GE service ports and 400GE fabric ports, S9701-82DC enables fault and performance monitoring, non-stop routing support for control and data plane, and comprehensive high-availability networks.

As a standalone router, the S9701-82DC can be deployed at the edge network to enable transport services over a scalable next generation telecom network. It provides 4GB deep buffering with 1000Mpps packet throughput and 2.4Tbs switching capacity. In addition, the S9701-82DC comes with integrated timing interfaces (GNSS, 10MHz, 1PPS, and ToD) for modern network applications.

When coupled with the UfiSpace fabric switch (S9705-48D), the S9701-82DC becomes a building block for a distributed disaggregated chassis (DDC). The DDC allows network service providers to implement a pay-as-you-grow model when scaling core network capacities, S9701-82DC cluster can scale from 2.4Tbps up to 134Tbps.



KEY BENEFITS

- Flexible capacity growth using horizontal scaling, pay-as-you-grow model
- Accelerated table lookup, packet buffering, and control memory with low latency high bandwidth memory
- Flexible and programmable packets processor
- High density ports with low power consumption
- Enable more highly scalable and flexible Core, Edge, and Central Office infrastructure
- Upstream connectivity management supported by flexibly configured fabric pipes
- Dynamic distribution and routing through automatic fault detection and recovery

KEY FEATURES

- Function as standalone or a cluster (2.8Tbps up to 134Tbps)
- Interoperable with S9700-53DX, S9700-23D and S9705-48D
- 4GB deep buffering and Intel Skylake-D 8 core at 1.9GHz
- Hardware supports full SyncE and IEEE1588v2 (T-GM, T-TC, T-BC/OC)
- Individual BMC allowing automatic and remote operations for monitoring and managing platform health status
- Hot swappable power supplies with 1+1 redundancy support
- Hot swappable fan modules with 3+1 redundancy support

SPECIFICATIONS

PHYSICAL

- ◆ 64 x 1/10/25GE SFP28 service ports
- ◆ 12 x 40/100GE QSFP28 service ports
- ◆ 6 x 400GE QSFP-DD fabric ports
- ◆ 1 x RJ45 + Micro USB serial console ports
- ◆ 1x USB 3.0 Type-A general purpose port
- ◆ 2 x 10GBase-X SFP+ management ports
- ◆ 1 x 10/100/1000M RJ45 management port

Processor Intel Skylake-D 8 Core @ 1.9GHz

Memory 64GB DDR4

Storage 128GB SSD

ASIC Broadcom Jericho2c BCM88802
Broadcom OP2 BCM16K (Optional)

BMC Aspeed AST2400

Timing 1 x GNSS input SMA
Interfaces 1 x 10MHz input/ output SMB
1 x 1PPS input/ output SMB
1 x ToD input RJ45

Hardware Stratum 3E OCXO
Timing ITU-T Synchronous Ethernet (SyncE)
Capabilities IEEE 1588v2 (Default, G.8265.1 G8275.1, G.8275.2),
T-TC, T-BC/OC, T-GM

Chassis 2RU, 436 x 609.6 x 87.7 mm
(WxDxH) 17.17 x 24 x 3.45 in.
Weight: 15.4 kg (34.03lbs)

Redundancy Hot swappable, 1+1 redundant PSU
Hot swappable, 3+1 redundant fans

ENVIRONMENTAL

Power Specs. AC input: 200 ~ 240V, 7.5A
DC input: -40 ~ -75V, 40A
Typical Power: 332.9 Watts (no transceiver)

Max. Operating Specs. Operating temperature: 0°C to 45°C (32°F to 113°F)
Operating humidity: 5% to 85% (RH), noncondensing

Max. Non-Operating Specs. Storage temperature: -40°C to 70°C (-40°F to 158°F)
Storage humidity: 5% to 93% (RH), non-condensing

PERFORMANCE

Switching Capacity 2.4 Tbps

Packet Buffer 4GB

REGULATORY COMPLIANCE

Safety UL 62368-1
IEC 60950-1
IEC/EN 62368-1

EMC FCC Part 15, Subpart B, Class A
ICES-003
EN 55032, Class A
EN 300 386
EN 55024
EN 55035
EN 61000-3-2
EN 61000-3-3

Specifications are subject to change without notice.

S9701-82DC

Telecom
Networking
Solutions

S9701-82DC Front and Rear Views



SUPPORTED ACCESSORIES

Transceivers

100GBASE QSFP28 SR4, 100GBASE QSFP28 LR4, 100GBASE QSFP28 ER4, 100GBASE QSFP28 ZR4,
25GBASE SFP28 SR, 25GBASE SFP28 LR, 25GBASE SFP28 ER, 25GBASE SFP28 ZR, 10GBASE SFP+ SR,
10GBASE SFP+ LR, 10GBASE SFP+ ER, 1GBASE SFP SX, 1GBASE SFP LX, 1GBASE SFP EX

Cable Types (Fabric port)

400GE QSFP-DD DAC(Direct Attach Cable), 400GE QSFP-DD AOC(Active Optical Cable),
400GE QSFP-DD AEC(Active Electric Cable)

Power Supply Types

1300W DC, front to back airflow, slim type, red colored latch
1300W AC, front to back airflow, slim type, red colored latch

Fan Types

Exhaust air flow, red colored latch

Rack mounting kit

Adjustable slide rail kit for systems on 19 in. width racks, support depth from
21 in. to 35 in.

