

# Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Tower, 120V, 8x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1500C

## Overview

**Presentation** Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

**Lead Time** Usually Ships within 2 Weeks

## Main

**Main Input Voltage** 120 V

**Other Input Voltage** 110 V  
125 V

**Main Output Voltage** 120 V

**Other Output Voltage** 110 V  
125 V

**Kw Rating** 1000 W

**Rated Power In Va** 1440 VA

**Input Connection Type** NEMA 5-15P

**Output Connection Type** 8 NEMA 5-15R

**Cable Length** 6 ft (1.83 m)

**Number Of Cables** 1

**Battery Type** Lead-Acid battery

**Provided Equipment** Installation guide  
USB cable

## Complementary

**Software Package** SmartConnect software for remote power monitoring feature availability varies by terms of use

## Batteries & Runtime

**Run Time** [View Runtime Graph](#)

**Efficiency** [View Efficiency Graph](#)

**Extendable Run Time** 0

**Included Battery Modules** 0

**Battery Slots Empty** 0

**Typical Recharge Time** 3 h

**Rbc Quantity** 1

**Battery Life** 3...5 year(s)

Replacement Battery	<a href="#">RBC7</a> 
Battery Charge Power (Watts)	136 W rated

## General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	Cloud-enabled monitoring
Redundant	No

## Physical

Color	Black
Height	8.62 in (21.9 cm)
Width	6.73 in (17.1 cm)
Depth	17.28 in (43.9 cm)
Net Weight	54.23 lb(US) (24.6 kg)
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	Yes

## Input

Efficiency At Full Load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic Distortion	Less than 5%
Maximum Configurable Power In Va	1440 VA
Max Configurable Power (Watts)	1000 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	cULus ENERGY STAR V2.0 (USA)
Equipment Protection Policy	Lifetime : \$150000

## Environmental

Acoustic Level	45 dBA
Heat Dissipation	225 Btu/h

<b>Operating Altitude</b>	0...10000 ft
<b>Ambient Air Temperature For Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature For Storage</b>	5...113 °F (-15...45 °C)
<b>Storage Altitude</b>	0...50000 ft (0.00...15240.00 m)
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>Control Panel</b>	Multi-function LCD status and control console
<b>Free Slots</b>	1
<b>Communication Port Support</b>	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

<b>Surge Energy Rating</b>	680 J
<b>Filtering</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

<b>Category</b>	11309 - APC RESALE PRODUCTS
<b>Gtin</b>	731304322795
<b>Returnability</b>	No

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	12.99 in (33 cm)
<b>Package 1 Width</b>	23.23 in (59 cm)
<b>Package 1 Length</b>	12.99 in (33 cm)
<b>Package 1 Weight</b>	59.92 lb(US) (27.18 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

## Sustainability


**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


## Resource performance

 Energy Efficient Product

 Take-Back Program Available

## Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

## Environmental Certifications

 Energy Star® ENERGY STAR UPS V2.0 (USA)

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65  
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Technical illustration

Dimensions

---

